



Features:

Four independent Digital Tuners in one chassis RBDS displays song titles and artists names High quality dim-able dot matrix display 36 FM station presets & 12 AM station presets Stereo or dual mono operation Easy to operate front panel controls Auto Scan automatically loads local stations Includes discrete code IR remote control RS232 controllable from a standard PC PC control includes free software GUI Front and back panel rotary volume controls Back panel 3.5mm IR port Color coded inputs and outputs Three year parts and labor warranty cTUVus and FCC listed

Included IR Remote



Optional V-RK2.5 Rack Kit





| Specifications | VT-1 | VT-4 | |
|-------------------------|--------------------|-----------------------|--|
| Tuner Specifications FM | | | |
| Line level Outputs | 2VRMS | 2VRMS | |
| Tuning Frequency | 87.5MHz to 108 MHz | 87.5MHz to 108 MHz | |
| Usable Sensitivity | Less than 12uv | Less than 15uv | |
| S/N ratio | Better than 50 dB | Better than 50 dB | |
| THD | 0.2 percent | 0.2 percent | |
| Frequency Response | 30Hz-15,000 Hz | 30Hz-15,000 Hz | |
| Stereo Separation | ≥30dB @ 1kHz | ≥30dB @ 1kHz | |
| Tuner Specifications AM | | | |
| Line level Outputs | 0. 5VRMS | 0. 5VRMS | |
| Tuning Frequency Range | 530kHz to 1710kHz | 530kHz to 1710kHz | |
| THD | 0.2 percent | 0.2 percent | |
| Usable Sensitivity | Less than 23uv | Less than 20uv | |
| S/N Ratio | Better than 48 dB | Better than 48 dB | |
| Others | | | |
| Rack Height | 2U | 2U | |
| Power Requirements AC | AC120V/60Hz | AC120V/60Hz | |
| Power Consumption AC | ≤10W | ≤10W | |
| Dimensions | 8.5"W*4"H*11.25"D | 8.5"W*4"*11.25D | |
| Shipping Weight | 2.5KG | 2.5KG | |
| Optional Accessories 1 | Rack Kit RK2.5 | Rack Kit RK2.5 | |