

Features:

- Hi fidelity 6.5" pendant or surface mount speaker system
- Suitable for indoor or outdoor use
- Dual front cabinet ports with extended bass response
- Excellent fidelity for music or voice
- 6.5 inch graphite woofer cone
- Rubber woofer surrounds
- 20oz ported Ferrite woofer magnet
- 1 inch Titanium dome tweeter
- Floating tweeter bridge
- Neodymium tweeter magnet
- PTZ tweeter protection with auto reset
- High quality crossover with air core inductor
- Aluminum non-rusting grille
- 15' aircraft type hanging cable and mounting hardware included
- Optional multi-position pivoting mounting bracket available
- Includes internal 40watt 25/70 volt transformer
- Easy wattage tap dial selector
- Transformer includes 8 ohm bypass setting
- Sold as each
- Master carton 2pcs
- 1 year warranty



Specifications:

- Diameter Woofer 6.5" (165.1mm) graphite
- 20oz Ferrite magnet
- Diameter Tweeter 1" (25.4mm) Titanium
- Neodymium tweeter magnet
- Power Handling 125watts (peak)
- Impedance 8 ohms (nominal)
- Frequency Response 60Hz - 22kHz (±5dB)
- Dispersion 100 °
- Sensitivity 90dB (1W 1M) Average
- Grille material Aluminum
- Color White

Included:

- Internal Transformer 40 watts 25/70 volt
- Wattage taps 40w, 20w, 10w, 5w & 8ohms
- Speaker end caps included
- Aircraft quality hanging cable 15' x 1
- Hanging hardware (inc)

Dimensions:

- Length 12" (304.8mm)
- Diameter Grille 8-5/8" (219.07mm)
- Diameter Mount 5" (127mm)
- Shipping Weight 11.5lbs (5.2kg) each
- Shipping Weight Master Carton (2pcs) 23lbs (10.4Kg)

New graphite woofer and titanium tweeter dual ported design



Includes hanging cable and clamps

included Gripple cable



Optional wall mount bracket available
VERSA-WMB

